

# UC-Insert *Normal Duty*

Bearing No.	Shaft Dia		Dimensions (Inches)								Load Rating		Wgt
	Inch	mm	D	B	C	S	S1	G	ds	F	Dynamic	Static	Lbs.
UC 201 -08	1/2												0.44
202 -10	5/8												0.42
204 -12	3/4												0.35
UC 201		12	1.8504	1.2205	0.6693	0.5000	0.7205	0.1770	1/4-28	0.1460	2900	1500	0.46
202		15											0.42
203		17											0.40
UC 204		20											0.35
UC 205 -14	7/8												0.49
205 -15	15/16		2.0472	1.3425	0.6693	0.5630	0.7756	0.1970	1/4-28	0.1540	3150	1800	0.44
205 -16	1												0.42
UC 205		25											0.42
UC 206 -18	1 1/8												0.75
206 -19	1 3/16		2.4409	1.5000	0.7480	0.6260	0.8740	0.1970	1/4-28	0.1970	4400	2540	0.71
206 -20	1 1/4												0.66
UC 206		30											0.66
UC 207 -20	1 1/4												1.15
207 -22	1 3/8		2.8346	1.6890	0.7870	0.6890	1.0000	0.2755	5/16-24	0.2240	5800	3450	1.06
UC 207		35											1.01
UC 208 -24	1 1/2												1.50
UC 208		40	3.1496	1.9370	0.8270	0.7480	1.1890	0.3150	5/16-24	0.2440	6630	4070	1.39
UC 209 -26	1 5/8												1.72
209 -28	1 3/4		3.3465	1.9370	0.8660	0.7480	1.1890	0.3150	5/16-24	0.2520	7100	4630	1.54
UC 209		45											1.50
UC 210 -30	1 7/8												1.87
210 -31	1 15/16		3.5433	2.0315	0.9449	0.7480	1.2835	0.3940	3/8-24	0.2560	7870	5210	1.76
210 -32	2												1.78
UC 210		50											1.72
UC 211 -32	2												2.69
UC 211		55	3.9370	2.1890	0.9843	0.8740	1.3150	0.3940	3/8-24	0.2760	9800	6570	2.36
UC 212 -36	2 1/4												3.64
212 -39	2 7/16		4.3307	2.5630	1.0630	1.0000	1.5630	0.3940	3/8-24	0.2990	10720	7400	3.13
UC 212		60											3.33
UC 213 -40	2 1/2												4.15
UC 213		65	4.7244	2.5630	1.1024	1.0000	1.5630	0.3940	3/8-24	0.3350	13000	9000	3.97
UC 215 -47	2 15/16												5.17
215 -48	3		5.1181	3.0630	1.1811	1.3110	1.7520	0.4720	7/16-20	0.3620	14830	11130	4.93
UC 215		75											4.86

FK BEARINGS



SL TYPE SEAL



L3 TYPE SEAL

