

No. **40** SS

1/2 PITCH, NOMINAL 0.284"



Single - Type B

Stainless Steel

Part No.	No. of	Outside	Bore		Hub		Wgt.
	Teeth	Diameter	Stock	Max	Dia.	L.T.B.	Lbs.
40B10SS	10	1.840	1/2	3/4	1 1/4*	7/8	0.28
40B11SS	11	2.000	1/2	13/16	1 3/8*	7/8	0.36
40B12SS	12	2.170	1/2	15/16	1 9/16*	7/8	0.44
40B13SS	13	2.330	1/2	1 1/16	1 9/16	7/8	0.50
40B14SS	14	2.490	1/2	1 1/8	1 11/16	7/8	0.60
40B15SS	15	2.650	5/8	1 1/4	1 13/16	7/8	0.68
40B16SS	16	2.810	5/8	1 3/8	2	7/8	0.82
40B17SS	17	2.980	5/8	1 7/16	2 1/8	1	1.06
40B18SS	18	3.140	5/8	1 1/2	2 5/16	1	1.24
40B19SS	19	3.300	5/8	1 3/4	2 1/2	1	1.42
40B20SS	20	3.460	5/8	1 7/8	2 5/8	1	1.60
40B21SS	21	3.620	5/8	1 7/8	2 3/4	1	1.68
40B22SS	22	3.780	5/8	1 7/8	2 7/8	1	1.81
40B23SS	23	3.940	5/8	2	3	1	2.18
40B24SS	24	4.100	5/8	2 1/4	3 1/4	1	2.20
40B25SS	25	4.260	5/8	2 1/4	3 1/4	1	2.30
40B26SS	26	4.420	5/8	2 1/4	3 1/4	1	2.40
40B28SS	28	4.740	5/8	2 1/4	3 1/4	1	2.75
40B30SS	30	5.060	5/8	2 1/4	3 1/4	1	2.88
40B35SS	35	5.860	5/8	2 1/4	3 1/4	1	3.32
40B40SS	40	6.650	3/4	2 3/8	3 1/2	1	4.28
40B45SS	45	7.450	3/4	2 3/8	3 1/2	1	4.68
40B60SS	60	9.840	3/4	2 3/8	3 1/2	1	7.00

*Has recessed groove in hub for chain clearance. Maximum bores shown will accommodate standard keyseat & setscrew over keyseat. Slightly larger bores are possible with no keyseat, shallow keyseat, or setscrew at an angle to keyseat.

