

No. 50 QD

5/8 PITCH, NOMINAL 0.343"



Single - Type QD - With Hardened Teeth

Part No.	No. of Teeth	Diameters		Bush- ing	Max. Bore	Dimensions						Wgt. Lbs.
		Outside	Pitch			L1	L2	C	Y	G	X	
50JA12H	12	2.710	2.415	JA								0.34
50JA13H	13	2.910	2.612	JA								0.40
50JA14H	14	3.110	2.809	JA	1 1/4	1 1/8	1 1/8	2 1/16	21/32	9/32	5/8	0.52
50JA15H	15	3.320	3.006	JA								0.60
50JA16H	16	3.520	3.204	JA								0.68
50SH17H	17	3.720	3.401	SH								0.84
50SH18H	18	3.920	3.599	SH	1 5/8	1 7/16	1 7/16	2 11/16	29/32	15/32	13/16	1.04
50SH19H	19	4.120	3.797	SH								1.24
50SDS20H	20	4.320	3.995	SDS								1.20
50SDS21H	21	4.520	4.194	SDS								1.32
50SDS22H	22	4.720	4.392	SDS								1.42
50SDS23H	23	4.920	4.590	SDS								1.58
50SDS24H	24	5.120	4.788	SDS								1.70
50SDS25H	25	5.320	4.987	SDS								1.86
50SDS26H	26	5.520	5.185	SDS								2.00
50SDS27H	27	5.720	5.384	SDS								2.12
50SDS28H	28	5.920	5.582	SDS	2	1 1/2	1 1/2	3 3/16	31/32	13/32	3/4	2.32
50SDS30H	30	6.320	5.979	SDS								2.64
50SDS32H	32	6.720	6.372	SDS								2.98
50SDS35H	35	7.320	6.972	SDS								3.62
50SDS36	36	7.520	7.171	SDS								3.64
50SDS40	40	8.320	7.966	SDS								4.74
50SDS42	42	8.720	8.363	SDS								5.40
50SDS45	45	9.310	8.960	SDS								5.90
50SDS48	48	9.910	9.556	SDS								6.66
50SK54	54	11.110	10.749	SK								9.68
50SK60	60	12.300	11.942	SK	2 5/8	2 1/8	2 1/8	3 7/8	1 17/32	29/32	1 1/4	11.88
50SK70	70	14.290	13.931	SK								15.52
50SK72	72	14.690	14.329	SK								16.44
50SF80	80	16.280	15.920	SF								19.90
50SF84	84	17.080	16.715	SF	2 15/16	2 1/4	2 1/4	4 5/8	1 21/32	29/32	1 1/4	22.98
50SF96	96	19.470	19.102	SF								29.88

