

# No. 80 SB

1" PITCH, NOMINAL 0.575"



## Single - Type B

Part No.	No. of Teeth	Diameters		Bore		Hub		Wgt. Lbs.	Part No.	Stock Bore	Wgt. Lbs.
		Outside	Pitch	Stock	Max	Dia.	L.T.B.				
80B8H	8	3.010	2.613	1	1	1 15/16*	1 5/8	1.40			
80B9H	9	3.350	2.924	1	1 5/16	2 1/4*	1 5/8	1.60			
80B10H	10	3.680	3.236	1	1 1/2	2 9/16*	1 5/8	2.20	80A10	15/16	1.00
80B11H	11	4.010	3.550	1	1 5/8	2 13/16*	1 5/8	3.20	80A11	15/16	1.30
80B12H	12	4.330	3.864	1	1 7/8	3 1/8*	1 5/8	3.40	80A12	15/16	1.50
80B13H	13	4.660	4.179	1	2	3	1 1/2	3.50	80A13	15/16	1.80
80B14H	14	4.980	4.494	1	2 1/4	3 1/4	1 1/2	4.10	80A14	15/16	2.20
80B15H	15	5.300	4.810	1	2 1/2	3 13/16	1 1/2	5.30	80A15	15/16	2.50
80B16H	16	5.630	5.126	1	2 3/4	4	1 1/2	5.90	80A16	15/16	2.90
80B17H	17	5.950	5.442	1	2 3/4	4	1 1/2	6.60	80A17	15/16	3.30
80B18H	18	6.270	5.759	1	2 3/4	4 1/4	1 1/2	7.30	80A18	15/16	3.70
80B19H	19	6.590	6.076	1	2 3/4	4 1/4	1 1/2	7.80	80A19	15/16	4.10
80B20H	20	6.910	6.392	1	2 3/4	4 1/4	1 1/2	8.40	80A20	15/16	4.70
80B21H	21	7.240	6.710	1	2 3/4	4 1/4	1 3/4	9.40	80A21	15/16	4.90
80B22	22	7.560	7.027	1	2 3/4	4 1/4	1 3/4	10.00	80A22	15/16	5.50
80B23	23	7.880	7.344	1	2 3/4	4 1/4	1 3/4	10.70	80A23	15/16	6.30
80B24	24	8.200	7.661	1	2 3/4	4 1/4	1 3/4	11.30	80A24	15/16	6.70
80B25	25	8.520	7.979	1	2 3/4	4 1/4	1 3/4	11.90	80A25	15/16	7.20
80B26	26	8.840	8.296	1 1/4	3 1/4	4 3/4	2	14.30	80A26	1 3/16	7.80
80B27	27	9.160	8.614	1 1/4	3 1/4	4 3/4	2	15.40	80A27	1 3/16	8.60
80B28	28	9.480	8.931	1 1/4	3 1/4	4 3/4	2	16.00	80A28	1 3/16	9.30
80B29	29	9.800	9.249	1 3/16	3 1/4	4 3/4	2	17.10	80A29	1 3/16	9.80
80B30	30	10.110	9.567	1 3/16	3 1/4	4 3/4	2	17.40	80A30	1 3/16	10.70
80B31	31	10.430	9.885	1 3/16	3 1/4	4 3/4	2	18.70	80A31	1 3/16	11.30
80B32	32	10.750	10.202	1 3/16	3 1/4	4 3/4	2	19.50	80A32	1 3/16	12.10
80B33	33	11.070	10.520	1 3/16	3 1/4	4 3/4	2	19.60	80A33	1 3/16	13.60
80B34	34	11.390	10.838	1 3/16	3 1/4	4 3/4	2	21.30	80A34	1 3/16	14.30
80B35	35	11.710	11.156	1 3/16	3 1/4	4 3/4	2	22.10	80A35	1 3/16	14.80
80B36	36	12.030	11.474	1 3/16	3 1/4	4 3/4	2	23.10	80A36	1 3/16	16.10
80B37	37	12.350	11.792	1 3/16	3 1/4	4 3/4	2	23.80	80A37	1 3/16	16.80
80B38	38	12.670	12.110	1 3/16	3 1/4	4 3/4	2	24.70	80A38	1 3/16	17.20
80B39	39	12.990	12.428	1 3/16	3 1/4	4 3/4	2	25.60	80A39	1 3/16	17.90
80B40	40	13.310	12.746	1 3/16	3 1/4	4 3/4	2	26.70	80A40	1 3/16	18.90
80B42	42	13.940	13.382	1 1/4	3 1/4	4 3/4	2	28.70	80A42	1 1/4	21.80
80B45	45	14.900	14.336	1 1/4	3 1/4	4 3/4	2	31.40	80A45	1 1/4	25.20
80B48	48	15.860	15.290	1 1/4	3 1/4	4 3/4	2	35.50	80A48	1 1/4	27.80
80B50	50	16.500	15.926	1 1/4	3 1/4	4 3/4	2	37.30	80A50	1 1/4	30.90
80B54	54	17.770	17.198	1 1/4	3 1/2	5 1/4	2	44.70	80A54	1 1/4	36.60
									80A56	1 1/4	39.40
80B60	60	19.680	19.107	1 1/4	3 1/2	5 1/4	2	54.50	80A60	1 1/4	45.30
80B72	72	23.500	22.926	1 1/2	4 1/4	6 1/4	2	75.00	80A72	1 1/2	65.70

\* Has recessed groove in hub for chain clearance. Maximum bores shown will accommodate standard keyway & setscrew over keyseat. Slightly larger bores are possible with no keyway, shallow keyway or setscrew at an angle to keyway. All sprockets are one piece construction.