

# No. 60 SS

3/4 PITCH, NOMINAL 0.459"



## Single - Type B

Stainless Steel

Part No.	No. of Teeth	Outside Diameter	Bore		Hub		Wgt. Lbs.
			Stock	Max	Dia.	L.T.B.	
60B10SS	10	2.760	3/4	1 1/8	1 15/16*	1 1/4	0.95
60B11SS	11	3.000	3/4	1 5/16	2 1/16*	1 1/4	1.20
60B12SS	12	3.250	3/4	1 3/8	2 3/8*	1 1/4	1.50
60B13SS	13	3.490	3/4	1 1/2	2 11/32	1 1/4	1.80
60B14SS	14	3.740	3/4	1 3/4	2 9/16	1 1/4	2.00
60B15SS	15	3.980	3/4	1 7/8	2 7/8	1 1/4	2.40
60B16SS	16	4.220	3/4	2	3 1/16	1 1/4	2.80
60B17SS	17	4.466	3/4	2 1/4	3 1/4	1 1/4	3.30
60B18SS	18	4.700	3/4	2 3/8	3 1/2	1 1/4	3.80
60B19SS	19	4.950	3/4	2 3/8	3 1/2	1 1/4	4.00
60B20SS	20	5.190	3/4	2 5/8	3 7/8	1 1/4	4.60
60B21SS	21	5.430	3/4	2 3/4	4	1 1/4	5.00
60B22SS	22	5.670	3/4	2 3/4	4	1 1/4	5.30
60B23SS	23	5.910	3/4	2 3/4	4	1 1/4	5.70
60B24SS	24	6.150	3/4	2 3/4	4	1 1/4	5.90
60B25SS	25	6.390	3/4	2 3/4	4	1 1/4	6.10
60B26SS	26	6.630	3/4	2 3/4	4	1 1/4	6.30
60B28SS	28	7.110	3/4	2 3/4	4	1 1/4	6.70
60B30SS	30	7.590	3/4	2 3/4	4	1 1/4	7.00
60B35SS	35	8.780	1	2 3/4	4	1 1/4	9.00
60B40SS	40	9.980	1	2 3/4	4 1/4	1 1/4	11.70
60B45SS	45	11.180	1	2 3/4	4 1/4	1 1/4	14.50
60B60SS	60	14.760	1 1/4	2 3/4	4 1/4	1 3/4	25.00

\*Has recessed groove in hub for chain clearance. Maximum bores shown will accommodate standard keyseat & setscrew over keyseat. Slightly larger bores are possible with no keyseat, shallow keyseat, or setscrew at an angle to keyseat.

