

# No. **80** SS

1" PITCH, NOMINAL 0.575"



## Single - Type B

Stainless Steel

Part No.	No. of Teeth	Outside Diameter	Bore		Hub		Wgt. Lbs.
			Stock	Max	Dia.	L.T.B.	
<b>80B10SS</b>	10	3.680	1	1	2 9/16*	1 5/8	2.20
<b>80B11SS</b>	11	4.100	1	1 5/16	2 13/16*	1 5/8	3.20
<b>80B12SS</b>	12	4.330	1	1 1/2	3 1/8*	1 5/8	3.40
<b>80B13SS</b>	13	4.660	1	1 5/8	3	1 1/2	3.50
<b>80B14SS</b>	14	4.980	1	1 7/8	3 1/4	1 1/2	4.10
<b>80B15SS</b>	15	5.300	1	2	3 13/16	1 1/2	5.30
<b>80B16SS</b>	16	5.630	1	2 1/4	4	1 1/2	5.90
<b>80B17SS</b>	17	5.950	1	2 1/2	4	1 1/2	6.60
<b>80B18SS</b>	18	6.270	1	2 3/4	4 1/4	1 1/2	7.30
<b>80B19SS</b>	19	6.590	1	2 3/4	4 1/4	1 1/2	7.80
<b>80B20SS</b>	20	6.910	1	2 3/4	4 1/4	1 1/2	8.40
<b>80B21SS</b>	21	7.240	1	2 3/4	4 1/4	1 3/4	9.40
<b>80B22SS</b>	22	7.560	1	2 3/4	4 1/4	1 3/4	10.00
<b>80B23SS</b>	23	7.880	1	2 3/4	4 1/4	1 3/4	10.70
<b>80B24SS</b>	24	8.200	1	2 3/4	4 1/4	1 3/4	11.30
<b>80B25SS</b>	25	8.520	1	2 3/4	4 1/4	1 3/4	11.90

\*Has recessed groove in hub for chain clearance. Maximum bores shown will accommodate standard keyseat & setscrew over keyseat. Slightly larger bores are possible with no keyseat, shallow keyseat, or setscrew at an angle to keyseat.

